

TrojanUVLogic™ Series

High Performance UV Systems

A robust, highly versatile UV water treatment system featuring the industry's most advanced low-pressure, high-output amalgam lamp technology is an efficient and cost effective alternative.

SHOWN
TUVLogic™
4L

INDUSTRIES | Aquaculture, Food & Bev.,
Life Sciences, Microelectronics, Rec. Waters

FLOWRATES: 230-7489GPM @ 95%UVT,
290-8141GPM @ 99%UVT



APPLICATIONS | Disinfection, Chlorine/
Chloramines Destruction, Ozone Destruction

DESIGN CAPABILITIES | Custom Configurations or
Skid Capabilities

TrojanUVLogic™ SERIES

The "L-shaped" reactor design was developed using advanced computer modeling, resulting in 40% greater hydraulic efficiency than conventional systems and features the industry's most advanced low-pressure, high-output (LPHO) amalgam lamp technology.

The TrojanUVLogic Series consists of a 316L stainless steel treatment chamber and a UL TYPE-3R 304 stainless steel control cabinet featuring a microprocessor-based controller. A maximum cable length of 15 feet (5m) is available. The compact size maximizes installation flexibility and preserves floor space with the ability to mount in line, horizontally or vertically.

Single-ended lamps and quartz sleeves allow for quick change-outs without tools. Select TrojanUVLogic™ systems are CE compliant as well as NSF 50 and cULus certified.

Aquafine TrojanUVLogic™ series for chlorine and chloramines utilizing amalgam lamp technology are the systems of choice for meeting the rigid quality standards of the Recreational Waters, Life Sciences and Food & Beverage markets.

AMALGAM TECHNOLOGY

Aquafine's TrojanUVLogic™ systems features the industry's most advanced low-pressure, high-output (LPHO) amalgam lamp technology and utilizes this advancement as an efficient and cost effective alternative across multiple applications. As a result, TrojanUVLogic systems require only one-third the number of lamps to deliver a dose equivalent to those of conventional systems.

SAFE & EFFECTIVE

UV does not 'add' anything to the water stream such as undesirable color, odor, chemicals, taste or flavor, nor does it generate harmful by-products. UV only imparts energy to the water stream in the form of ultraviolet light to reduce the chlorine or chloramines present.

For questions regarding your application needs, please contact your local Authorized Distributor or Aquafine Corporation for more information.



Aquafine®
60 Years of Pure Quality

TrojanUVLogic™ Series

High Performance UV Water Treatment System

Model: TrojanUVLogic™	02AS20††	03AS20	04AS20	03AL20††	06AS20	04AL20††	08AS20	06AL20	08AL20	06AL30	08AL30	12AL30	12AL40	18AL40	18AL50††	24AL50††	30AL50††	
MAXIMUM FLOW RATE																		
DISINFECTION @95%UVT GPM (M³/HR)*	230 (52)	350 (80)	480 (110)	560 (130)	695 (160)	780 (177)	875 (200)	852‡ (194)	1014‡ (230)	1750 (400)	2270 (516)	2765 (628)	3643 (828)	4005 (910)	6145 (1396)	8141 (1850)	7489 (1702)	
DISINFECTION @99% UVT GPM (M³/HR)*	290 (66)	430 (97)	585 (133)	690 (156)	835 (189)	935 (212)	1010 (229)	1014‡ (230)	1040§ (236)	2275 (517)	2240‡ (509)	2730‡ (620)	3989 (906)	4750** (1080)	7320‡ (1664)	8141§ (1850)	8141†† (1850)	
OZONE DEST. @99% UVT GPM (M³/HR)†	100 (23)	145 (32)	195 (44)	235 (53)	280 (63)	320 (72)	345 (78)	450 (102)	546 (124)	760 (173)	990 (225)	1240 (282)	1772 (403)	2589 (588)	3253 (739)	4292 (975)	5265 (1196)	
NUMBER OF UV LAMPS (LP)	2	3	4	3	6	4	8	6	8	6	8	12		18		24	30	
ELECTRICAL REQUIREMENTS																		
ELECTRICAL SUPPLY	208-240VAC 50Hz SINGLE PHASE 1 W + GND, 60Hz SINGLE PHASE 2 W + GND																	
OPERATING POWER (NOMINAL WATTS)	346	534	692	849	1007	1113	1323	1639	2170	1639	2170	3218		4750		6310	7870	
BALLAST TYPE	ELECTRONIC																	
CONTROLLER																		
UV SENSOR W/ 4-20mA	STANDARD																	
LAMP STATUS INDICATOR	STANDARD																	
LAMP OUT ALERT DRY CONTACT	STANDARD																	
TEMP. SWITCH	STANDARD																	
RUNNING TIME INDICATOR	STANDARD																	
REMOTE ON/OFF 24-240V AC/DC	STANDARD																	
CONTROL CABINET (CC)																		
CC SYSTEM RATING	NEMA 12																	
MATERIALS OF CONSTRUCTION	304 STAINLESS STEEL (PAINTED CARBON STEEL OPTIONAL)																	
CC DIMENSIONS - HXWXD INCHES (CONTACT AQUAFINE FOR CE)	24 X 24 X 10						24 X 30 X 10	24 X 24 X 10	24 X 30 X 10	24 X 24 X 10	24 X 30 X 10				48 X 36 X 10			
TREATMENT CHAMBER																		
MATERIALS OF CONSTRUCTION	316L STAINLESS STEEL																	
INTERNAL SURFACE FINISH	Ra 32 (Ra 15 OPTIONAL)																	
OPERATING TEMPERATURE °F (°C)	Water: 41° - 104° (5° - 40°) Ambient Air: 34° - 104° (1° - 40°)																	
MAX. OPERATING PRESSURE PSI (BAR)	150 (10)																	
INLET/OUTLET FLANGE INCHES (MM)	4 (100)		6 (150)						10 (250)			14 (350)		18 (450)				
WIPER OPTION	MANUAL	MANUAL OR AUTOMATIC									AUTOMATIC							

Dose Levels: * 30 mJ/cm² after 9,000 hours of operation. † 90 mJ/cm² after 9,000 hours of operation. ‡ 40 mJ/cm² after 9,000 hours of operation. § 47 mJ/cm² after 9,000 hours of operation. ** 49 mJ/cm² after 9,000 hours of operation. †† 58 mJ/cm² after 9,000 hours of operation.

‡† These models are not NSF certified. For more information, contact Aquafine.



North America & International
29010 Ave Paine, Valencia, CA 91355
P 661 257 4770 F 661 257 2489
sales@aquafineuv.com www.aquafineuv.com

Europe
Ramskamp 77-85 D-25337 Elmshorn, Germany
P +49 4121 57806 13 F +49 4121 57806 30
saleseu@aquafineuv.com www.aquafineuv.com



Aquafine is an ISO 9001:2008 certified company.

All specifications are subject to change without notice.
For additional requirements, please contact Aquafine Corporation.